



## HIGH-IMPACT PRINTS. HIGH-IMPACT PROFITS.



**Verve LED 2513 X** enables high quality direct printing on almost any kind of materials, including wood, glasses, leather, ceramic tiles & much more.

High-quality, productive colour scheme with groundbreaking features:



Models			K	(L2513F	2	K	L2513R	86	KL2	513M	
Printing Technology			Drop-on-demand, Piezo Electric Inkjet								
Print Heads			Ricoh Gen 5, Ricoh Gen 6, Konica Minolta 1024 Atom								
No. of Print Heads			2 to 12 (7 PL) 2 to 12 (5 PL				PL)	L) 4 to 15 (6 PL)			
		Size	2.55 m x 1.35 m								
Media		Thickness	Maximum 100 mm								
		Handling	Suction								
Printing size			2.5 m x 1.3 m								
Curing System			Quad UV LED lamps								
		Туре	UV LED Curable Ink								
Ink		System	Bulk Ink Refillable System								
		Colors	CMYK + W+ V								
Printing Resolution (dots per inch)			Upto 1200 dpi						Upto 1440 dpi		
Connectivity/Interface			USB 3.0								
Power Requirements			AC 220 V, 30 A, 50/60 Hz								
Dimensions (Printer only)			4660 x 2180 x 1480 mm								
Dimensions (With Packing)			4830 x 2380 x 1900 mm								
RIP software				Onyx (ColorJet Edition)							
Weight (Net Weight/Gross Weight) kgs				1650 / 1850							
Environmental		Power ON	Temperature: 18 to 28°C Humidity: 20 to 60% RH (Non-condensing)								
		Power OFF	Temperature: 5 to 40 °C Humidity: 20 to 80% RH (Non-condensing)								
				Print Speed (Sqm/hr)							
			KL2513R		KL2513R6			KL2513M			
Modes	Print DPI	Passes	1 ROW	2 ROW	3 ROW	1 ROW	2 ROW	3 ROW	1 ROW	2 R0	
Mode 1	726 x 900	6	15	27	41						
Mode 2	726 x 1200	8	12	22	32						
Mode 1	726 x 600	4				32	53	68			
Mode 2	726 x 900	6				22	39	52			
Mode 1	540 x 720	4							34	6	
Mode 2	540 X 1080	6							23	4	
Mode 3	540 x 1440	8							17	30	



CMYK	
ly for	
are on	
speeds	
t peak	
*Gradien	

